



## SMART CONSTRUCTION. BUILT TO LAST.

Designed to haul medium duty, low profile equipment, Trail King's Tilt Utility trailer is the highest quality and dependable tilt bed on the market. All TKTU models offer a 4' stationary deck and 16' tilt deck with capacity ranging from 12,000-lb. to 16,000-lb.

The TKTU is manufactured with highest standard of craftsmanship making it a trailer that will last for the long haul. Commit to a product that can stand up to the daily challenges you face.

Find your nearest dealer: [www.TrailKing.com/DealerLocator](http://www.TrailKing.com/DealerLocator)

PEOPLE. PRODUCT. PERFORMANCE.

## COMPREHENSIVE SUPPORT. UNMATCHED SERVICE.

*Whether you own a premium Trail King trailer or you are looking to own one, you can still have access to our comprehensive PEAK PERFORMANCE™ Aftermarket Programs:*



**Instantly access** over 10,000 on-hand parts and a variety of online tools. All Trail King Certified dealers, fleets, and serviced facilities can place same-day shipping orders for convenient and efficient ordering. Customers looking for more information can contact a local Trail King dealer or submit direct inquiries to [trailkingpartssupport@trailking.com](mailto:trailkingpartssupport@trailking.com).



**Extend the life** of your trailer and increase future resale value by restoring it to near-peak performance through Trail King's factory refurbishment program. Customers can request a free estimate for comprehensive refurbishments or specified repairs by visiting [www.tkpeakperformance.com](http://www.tkpeakperformance.com). Our expert technicians specialize in Trail King equipment, but we also welcome other trailer brands.



**Competitive rates and flexible terms** designed to make a Trail King purchase affordable, convenient, and secure. Trail King's innovative payment program operates with an understanding of the changing demands a customer's business faces. Our full suite of financing structures, including Loans, Finance Leases, and TRAC Leases, makes it easier than ever before to own a Trail King trailer.

**Trail King** is the leading manufacturer of open deck and materials hauling trailers for the asphalt paving, construction, commercial hauling, agriculture, and specialized transport industries. With a network of almost 400 dealer locations across the U.S. and Canada, Trail King is there when you need us. Our dedicated teams of customer service professionals are available 24/7 to serve you.

We know that your bottom line is important to you and it's our commitment to make sure you achieve the lowest cost of ownership with the highest quality trailers offered in the market.

**A Trail King trailer won't just get the job done — it will get the job done *right*.**



**TRAIL KING**  
WE'VE GOT YOUR BACK.



[TrailKing.com/TKTiltUtility](http://TrailKing.com/TKTiltUtility)

300 East Norway Ave. Mitchell, SD 57301 | 800-843-3324 | [www.trailking.com](http://www.trailking.com)

© 2015 Trail King Industries. All rights reserved.

OPEN-DECK  
CONSTRUCTION  
**TILT  
UTILITY**  
TRAILER



# TKTU



**TRAIL KING**  
WE'VE GOT YOUR BACK.





STANDARD FEATURES

**Safety Chains**  
Heavy-duty safety chains with GVWR-rated grab hooks are built tough for years of dependable service.

**Drop Leg Jack**  
Bolt-on 12,000-lb jack with drop leg.

**Heavy-Duty Bent D-Rings**  
Forged D-rings for your trailer to handle even your toughest hauling requirements.

**Axles, Tires, Fender**  
Torflex axles, 8-hole wheels, and radial tires deliver a smooth ride, long service life, and attractive appearance.

**I-Beam Crossmembers**  
Full width I-beam crossmembers are used to provide maximum load bearing strength. 2-part polyurethane primer is completed prior to adding the deck to provide corrosion resistance in unseen areas.



TKTU STANDARD EQUIPMENT	TKT12U	TKT14U	TKT16U
Payload Capacity	12,000 lb.	14,000 lb.	16,000 lb.
Structural Steel Main Frame	X	X	X
Overall Width	102"	102"	102"
Deck Width between Fenders	82"	82"	82"
Overall Deck Length	20'	20'	20'
Stationary Deck Length	4'	4'	4'
Tilt Deck Length	16'	16'	16'
Loaded Deck Height	23"	23"	23"
Torflex Axles	(2) 7,000 lb.	(2) 7,000 lb.	(2) 8,000 lb.
Electric Brakes on All Axles	X	X	X
12,000 HD Jack with Spring Foot	X	X	X
4-Bolt Pintle Hitch, adjustable range	19" - 23.5"	19" - 23.5"	19" - 23.5"
6 pair Bent D-Rings: (2) on Stationary / (4) on Tilt Deck	X	X	X
14 Gauge Fenders	X	X	X
Single Disc Wheel (8-Hole)	X	X	X
Tires	235/80R x 16	215/75R x 17.5	215/75R x 17.5
1.5" Oak (Raised) Decking	X	X	X
Electrical System per DOT Regulations	X	X	X
Safety Chains with Grab Hooks	X	X	X
Headboard	X	X	X
Breakaway Switch	X	X	X
Red & White Conspicuity Markings	X	X	X
Trail King 2-Part Polyurethane Primer & Paint	X	X	X

**\*See your local dealer for full list of available options.**



**Adjustable Hitch**  
Accommodate a wide variety of towing vehicles with an adjustable 4-bolt hitch rated for the full GVWR of the trailer.



**Toolbox**  
Spacious toolbox spans the entire width of the tongue area for enough room to store all your chains and tools.



**Break-Away System**  
The lighted read-out break-away system monitor provides easy and convenient monitoring of the charge status.



**Safety Headboard**  
The safety headboard provides extra dimension of safety and load-hauling security.



**Oak Decking**  
All TKTU models come with 1.5" nominal oak decking that is double screwed to crossmembers to prevent cupping. This deck will stand up to years of rugged service.



**Recessed Dot Lights**  
Recessed lights at the rear are long-lasting and provide improved safety and visibility.



**Platform Lock**  
Keep your deck from accidentally tilting while in the transport mode with the platform lock mechanism and safety lock pin.



**Platform Cushioning Cylinders**  
Single platform cushioning cylinders make loading and unloading a smooth operation.



**Approach Plate**  
The main deck tilts to an 11° load angle, and features star traction material on the approach plate and recessed lights that are protected during the loading/unloading process.

Products shown may feature optional equipment. Available specifications are subject to change without notice.