

MORBARK® BEEVER™ M12RX



BENEFITS

- With its power and easily transportable design, this compact and economical chipper is the ideal unit for utility line clearing, residential tree services, rental yards and municipalities.
- The dual-sided, chambered air impeller system increases chip-throwing velocity and reduces dust and material blowback out the infeed to pack more into the chip truck.
- The 18" diameter single top feed wheel easily climbs over material, reduces drag and increases chipping efficiency.
- Like all Morbark equipment, the M12RX is a long-lasting, durable machine backed by a world-class parts and service support team.



Infeed Opening

The 60" wide x 31" high chute opening and 15" wide x 12" high throat opening allows for easy feeding of branchy material and reduced saw labor.



Drive Belt Cover

Drive belt inspection cover provides easy access for drive system maintenance.



Feed Wheel

TorqMax™ Top Feed Wheel
Compression system with spring-assisted down pressure generates more than 3,200 lb./ft. of material pulling force.



New-Style Discharge

360° swivel discharge with chip deflectors puts chips right where they're needed without removing the Beever from the tow vehicle.

SPECIFICATIONS

SPECIFICATIONS MAY VARY WITH EQUIPMENT OPTIONS 5/14/15

General

Chipping capacity 12"
Height 9'
Width 5'11"
Length 15'4"
Gross weight (approximate) 5,200 lbs.
Suspension 6,000 lb. torsion
Infeed opening 60" wide x 31" high
Throat opening 15" wide x 12" high
Drum 14 1/4" wide x 21 3/8" diameter
Engine GM
Horsepower 89 HP
Fuel capacity 24 1/2 gallons
Hydraulic capacity 17 gallons
Frame 8.2 lb., 6" channel
Tires (2) 235/80R16"
Hitch 2 1/2" Pintle

Equipment Highlights

21 3/8" diameter x 14 1/4" wide staggered-knife-pocket drum with two dual-edged chipper knives and dual-sided chambered air impeller system
Reversing automatic feed system
Enclosed engine with gauge panel, radiator fines screen and slide rails for belt adjustment
Fuel tank sight gauge and drain plug
Hydraulic tank shut-off valve, drain plug and clean-out cover
Live hydraulics; ball valve, pump, motor and control valve
Tube and support pad to mechanically raise and lower feed wheel using the drawbar jack
5" x 3" tubular steel telescoping drawbar with two 12" extensions

Additional Features

Morthane Paint System: A chemically cured, electrostatically applied urethane coating with high-gloss finish, built-in UV protection, chip and chemical resistance and corrosion protection

Options Include

ChipSafe® Operator Safety Shield
Bottom Bump Bar



MORBARK®
BUILDING EQUIPMENT THAT CREATES OPPORTUNITIES

800.831.0042
989.866.2381
www.morbark.com

PO Box 1000
8507 S. Winn Rd.
Winn, MI 48896