

MORBARK® BEEVER™ M12R



BENEFITS

- With its power and easily transportable design, this compact and economical chipper is the ideal unit for utility line clearing, residential tree services, rental yards and municipalities.
- The dual-sided, chambered air impeller system increases chip-throwing velocity and reduces dust and material blowback out the infeed to pack more into the chip truck.
- The direct driven dual feed wheel system with serrated teeth and knife bar combination and end cap ripper teeth allow positive material feeding and reduced material wrapping around the feed wheel shaft for increased feeding efficiency.
- Like all Morbark equipment, the M12R is a long-lasting, durable machine backed by a world-class parts and service support team.



Infeed Opening

The 60" wide x 31" high chute opening and 15" wide x 14" high throat opening allows for easy feeding of branchy material and reduced saw labor.



Drive Belt Cover

Drive belt inspection cover provides easy access for drive system maintenance.



Hydra-Lift System

The powerful Hydra-Lift™ dual feed wheel compression system with spring-assisted down pressure generates more than 3,300 lb./ft. of combined material pulling force.



360° Swivel Discharge

360° swivel discharge with chip deflectors puts chips right where they're needed without removing the Beever from the tow vehicle.

SPECIFICATIONS

SPECIFICATIONS MAY VARY WITH EQUIPMENT OPTIONS 10/22/15

General

Chipping capacity 12"
 Height 8'5"
 Width 5'11"
 Length 15'5"
 Gross weight (approximate) 5,500 lbs.
 Suspension 6,000 lb. Torflex
 Infeed opening 60" wide x 31" high
 Throat opening 15" wide x 14" high
 Drum 14 1/2" wide x 21 3/8" diameter
 Engine CAT, GM, John Deere, Kubota or Perkins
 Horsepower 49–130 HP
 Fuel capacity 24 1/2 gallons
 Hydraulic capacity 17 gallons
 Frame 8.2 lb., 6" channel
 Tires (2) 235/80R16"
 Hitch 2 1/2" Pintle Ring

Equipment Highlights

14 1/2" wide x 21 3/8" diameter staggered-knife-pocket drum with two dual-edged chipper knives and dual-sided chambered air impeller system
 Top and bottom horizontal feed wheels equipped with serrated teeth and knife bars
 Reversing automatic feed system
 Enclosed engine with gauge panel, radiator fines screen and slide rails for belt adjustment
 Fuel tank sight gauge, drain plug and shut-off valve
 Hydraulic tank shut-off valve, drain plug and clean-out cover
 Live hydraulics; ball valve, pump, motor and control valve
 3" x 5" tubular steel telescoping drawbar with two 12" extensions

Additional Features

Morthane Paint System: A chemically cured, electrostatically applied urethane coating with high-gloss finish, built-in UV protection, chip and chemical resistance and corrosion protection

Options Include

ChipSafe® Operator Safety Shield
 Folding infeed tray
 Winch package: heavy-duty, 5,000 lb. pull capacity with rope and 10' chafe guard
 Custom paint and logo packages
 Bottom Bump Bar
 Hydraulic Swivel Discharge
 Cone Holder
 Flow Control
 Axle Options Available
 Fender Options Available
 Battery Box Options Available



MORBARK®
 BUILDING EQUIPMENT THAT CREATES OPPORTUNITIES

800.831.0042
 989.866.2381
 www.morbark.com

PO Box 1000
 8507 S. Winn Rd.
 Winn, MI 48896