

# MORBARK® BEEVER™ M15R

## BENEFITS

- Ideal for residential tree services, utility line clearing, vegetation management, maintenance contractors and municipalities, this high-capacity, high-production chipper includes more standard features than any other chipper in its class.
- The powerful TorqMax™ dual feed wheel compression system generates more than 6,600 lb./ft. of material pulling force.
- Unit is pre-plumbed and outfitted for the easy installation of most aftermarket components.
- Ergonomic infeed design provides consistent feed control bar activation.
- Like all Morbark equipment, the M15R is a long-lasting, durable machine backed by a world-class parts and service support team.



### Drum

30" diameter four-knife staggered-knife-pocket drum with patented removable knife holders provides maximum chipping efficiency.



### Channel Frame

The 8.2 lb., 6" channel frame rails with 2" x 6" tubular steel frame with cross bracing increases structural strength while maintaining low unit weight.



### Reversing Auto-feed

The reversing auto-feed system automatically stops forward feed and briefly backs material away from the drum for optimum engine performance while chipping.



### Hydraulic Down Pressure

The Variable Force™ Hydraulic Down Pressure System eliminates the use of springs and creates up to 4,500 lbs. of perpetual down pressure.

## SPECIFICATIONS

SPECIFICATIONS MAY VARY WITH EQUIPMENT OPTIONS 10/22/15

### General

Chipping capacity . . . . . 15"  
 Height . . . . . 8'11"  
 Width . . . . . 7'3"  
 Length . . . . . 18'1"  
 Gross weight (approximate) . . . . . 8,900 lbs.  
 Suspension . . . . . 9,000 lb. Torflex  
 Infeed opening . . . . . 56" wide x 37" high  
 Throat opening . . . . . 20 1/2" wide x 18" high  
 Drum . . . . . 23 3/4" wide x 30" diameter  
 Engines . . . CAT, Cummins, GM, John Deere, Perkins  
 Horsepower . . . . . 130–174 HP  
 Fuel capacity . . . . . 32 gallons  
 Hydraulic capacity . . . . . 12 gallons  
 Frame . . . . . 8.2 lb., 6" channel  
 Tires . . . . . (2) 215/75R17 1/2"  
 Hitch . . . . . 2 1/2" Pintle Ring

### Equipment Highlights

Dual horizontal feed wheels with TorqMax top feed wheel compression system, hydraulic lift assist, Variable Force constant hydraulic down pressure system with additional manually applied hydraulic down pressure at the valve handle and direct-drive bottom feed wheel with torque arm coupler

Live hydraulic system including: ball valve, pump, motor, and valve bank with additional pre-plumbed valve section for installation of an aftermarket winch package

3" x 5" tubular steel telescoping drawbar with two 12" extensions

Morthane Paint System: A chemically cured, electrostatically applied urethane coating with high-gloss finish, built-in UV protection, chip and chemical resistance and corrosion protection

### Options Include

ChipSafe® Operator Safety Shield  
 Winch package: heavy-duty, 5,000 lb. pull capacity with rope and 10' chafe guard  
 Bottom Bump Bar  
 Hydraulic Swivel Discharge  
 Cone Holder  
 Spare Tire/Mount  
 Folding Infeed Tray  
 Flow Control  
 Axle Options Available  
 Fender Options Available  
 Battery Box Options Available



**MORBARK®**  
 BUILDING EQUIPMENT THAT CREATES OPPORTUNITIES

800.831.0042  
 989.866.2381  
 www.morbark.com

PO Box 1000  
 8507 S. Winn Rd.  
 Winn, MI 48896