



JOHN DEERE



ROTARY TILLERS

RT52 | RT66



WORKSITE PRO™

COMMERCIAL WORKSITE PRODUCTS

SPECIFICATIONS

RT52 / RT66

- RT52 and RT66 till up to a 6-inch (15 cm) depth. Rugged construction and heavy-duty tines provide long service life and excellent operation in all conditions.
- Offset to the right 6 inches (15 cm), both models are ideal for close tilling beside walls and sidewalks. The RT66 can also be positioned in the center.
- Tillers require only standard hydraulic flow for high-quality performance.
- For increased efficiency, till in both forward and reverse directions.
- Optional scarifiers increase productivity in hard ground conditions.
- Like all Worksite Pro™ attachments, these tillers are optimized to work with John Deere 300-Series Skid Steers and Compact Track Loaders, and are compatible with most competitive models. Plus, they're backed by a one-year warranty and one-of-a-kind parts and service. See your local John Deere CWP dealer for details.

RT52

RT66

Compatibility	317, 320, 325, 328, 332, CT322, and CT332	317, 320, 325, 328, 332, CT322, and CT332
Tilling width	52 in. (1.3 m)	66 in. (1.7 m)
Overall width	62 in. (1.6 m)	76 in. (1.9 m)
Overall length	48 in. (122 cm)	48 in. (122 cm)
Overall height	35 in. (89 cm)	35 in. (89 cm)
Tilling depth	6 in. (15 cm)	6 in. (15 cm)
Number of tines	24	32
Number of scarifiers (optional)	4	5
Minimum hydraulic flow	18 gpm (68 lpm)	18 gpm (68 lpm)
Maximum hydraulic flow	28 gpm (106 lpm)	28 gpm (106 lpm)
Operating weight	750 lb. (340 kg)	1,000 lb. (454 kg)

www.JohnDeere.com

WORKSITE PRO™



This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

