


Aerial Work Platforms

IWP® Super Series™

Specifications



Models	IWP-20S		IWP-25S		IWP-30S	
Measurements	US	Metric	US	Metric	US	Metric
Working height*	26 ft 3 in	8.10 m	30 ft 11 in	9.42 m	35 ft 6 in	10.8 m
Platform height	20 ft 3 in	6.17 m	24 ft 11 in	7.6 m	29 ft 6 in	9 m
A Horizontal outreach**	2 ft 2 in	0.61 m	—	—	—	—
B Height - stowed:						
fully lowered	6 ft 4 in	1.93 m	6 ft 4 in	1.93 m	6 ft 4 in	1.93 m
base raised	6 ft 6 in	1.98 m	6 ft 6 in	1.98 m	6 ft 6 in	1.98 m
C Length	5 ft	1.52 m	5 ft	1.52 m	5 ft	1.52 m
D Width - standard base	2 ft 8 in	0.81 m	2 ft 8 in	0.81 m	—	—
wide base	—	—	—	—	3 ft 4 in	1.02 m
Corner access***	6 in	0.15 m	6 in	0.15 m	7 in	0.18 m

Productivity

Lift capacity:	350 lbs	159 kg	350 lbs	159 kg	350 lbs	159 kg
AUS/ANSI/CE with outreach option	300 lbs	136 kg	—	—	—	—
Platform Dimensions (l/w/h)						
Standard	27/26/44.75 in	69/66/114 cm	27/26/44.75 in	69/66/114 cm	27/26/44.75 in	69/66/114 cm
Gated standard	27/26/44.75 in	69/66/114 cm	27/26/44.75 in	69/66/114 cm	27/26/44.75 in	69/66/114 cm
Gated narrow	26/20/44.75 in	66/51/114 cm	26/20/44.75 in	66/51/114 cm	26/20/44.75 in	66/51/114 cm
Standard fiberglass**	29/26.5/43.5 in	74/67/110 cm	29/26.5/43.5 in	74/67/110 cm	29/26.5/43.5 in	74/67/110 cm

Power

AC models	110 V / 50-60 Hz or 220 V / 50-60 Hz
DC models	12V

Weight****

Standard base

ANSI/CSA (AC)	1,245 lbs	564 kg	1,290 lbs	585 kg	—	—
ANSI/CSA (DC)	1,345 lbs	610 kg	1,390 lbs	630 kg	—	—
CE (AC)	1,245 lbs	565 kg	1,290 lbs	585 kg	—	—
CE (DC)	1,345 lbs	610 kg	1,390 lbs	630 kg	—	—

Standard base with outreach option

ANSI (AC)	1,350 lbs	612 kg	—	—	—	—
ANSI (DC)	1,450 lbs	658 kg	—	—	—	—
CE (AC)	1,350 lbs	612 kg	—	—	—	—
CE (DC)	1,450 lbs	658 kg	—	—	—	—

Wide base

ANSI (AC)/CSA	—	—	—	—	1,430 lbs	649 kg
ANSI (DC)/CSA	—	—	—	—	1,530 lbs	694 kg
CE (AC)	—	—	—	—	1,430 lbs	649 kg
CE (DC)	—	—	—	—	1,530 lbs	694 kg

Standards Compliance

ANSI A92.3, CSA B354.1, EN 280, AS 1418.10

* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.

** Fiberglass platforms are not available with the outreach option.

*** Corner of platform top rail to corner of wall with ability to rotate leveling jack handle.

**** Weight will vary depending on options and/or country standards.

Features

Standard Features

Measurements

IWP-20S

- 26 ft 2 in (8.15 m) working height
- 20 ft 2 in (6.15 m) platform height
- 2 ft 8 in (0.81 m) standard base width
- Outreach option adds 2 ft 2 in (0.66 m) of horizontal reach
- Up to 350 lbs (159 kg) lift capacity

IWP-25S

- 30 ft 5 in (9.44 m) working height
- 24 ft 5 in (7.44 m) platform height
- 2 ft 8 in (.81 m) standard base width
- Up to 350 lbs (159 kg) lift capacity

IWP-30S

- 35 ft 6 in (11 m) working height
- 29 ft 6 in (9 m) platform height
- 3 ft 4 in (1.02 m) wide base width
- Up to 350 lbs (159 kg) lift capacity

Productivity

- Standard base (IWP[™]-20S and 25S only)
- Sliding mid-rail standard platform
- Auxiliary platform lowering
- Most rigid mast in the industry
- Standard base rolls through standard doorways
- Wide base rolls through double doorways
- AC power to platform
- Dual activated up/down switch
- Ground fault interrupter lower receptacle
- Tie down attachment points
- Overhead crane attachment point
- Wide forklift pockets
- Built-in level sensing with interlocks

Power

- AC power 110V / 50-60 Hz
- AC power 220V / 50-60 Hz
- DC power with worldwide automatic "smart" charging system (12V / 110V / 230V / 50-60 Hz)

Options & Accessories

Productivity

- Outreach option (IWP-20S only) (not available for CSA)
- Operational warning light and descent alarm package (mandatory for CE and AUS)
- Tool tray
- Fluorescent tube caddy
- Platform locating laser light

Power

- Power wheel assist with dual battery package*
- Dual battery package
- DC power 85V, 110V or 220V / 50-60 Hz

Platform

- Gated standard platform
- Gated narrow platform
- Standard fiberglass platform

Base

- Wide base (IWP[™]-30 only)

* Adds 12.5 in (.32 m) to unit length and 285 lbs (129 kg) to unit weight



Shown with optional power wheel assist

Genie United States

6464 185th Ave. NE
Redmond, WA 98052
Telephone +1 (425) 881-1800
Toll Free in USA/Canada +1 (800)-536-1800
Fax +1 (425) 883-3475

Distributed By: